



*GRAYWALL*TM

Affordable Waterproofing

All Rubber • Highly Elastic • No Asphalt • Seamless Protection • Economical • Warranted



GRAYWALL™

WATER

GRAYWALL™ WATERPROOFING
is an all-rubber polymer product applied as a single component spray by certified applicators to provide a seamless elastomeric membrane. GRAYWALL is non-toxic when cured and contains no asphalt to leach into and contaminate our groundwater.

GRAYWALL™ was engineered to provide excellent adhesion and crack bridging “elasticity” for the toughest commercial and residential jobs. GRAYWALL is BOCA listed (93-22) and exceeds the most stringent standards for use as an air vapor barrier.

GRAYWALL's warranted* high performance and low cost have made it a frequently specified product worldwide.

*Warranty varies regionally. Contact your certified RUB-R-WALL™/GRAYWALL™ applicator for a copy of the warranty available in your area.



PROOFING

Product Specifications

PROPERTY	TEST METHOD	TYPICAL RESULT FOR GRAYWALL
Elongation	ASTM D 412 (die c)	1400+ percent
Low Temperature Flexibility	Bend around 0.5" Mandrel	Flexible to -20° F
Asphalt Content	GPC	0.0 percent
180 Degree Peel Adhesion	Metal Plate	18lb. per inch
Liquid Water Absorption	ASTM D95	Less than 0.5 percent
Resistance to Bacteria	ASTM D42 99-83 (modified)	No Attack
Resistance to Degradation in Soil	ASTM E-154 (soil preparation)	Excellent
Resistance to Algae	ASTM G2975 (modified)	No Attack
Resistance to Fungus	ASTM D2020 (modified)	No Attack

