

Step on the gas. GX 120 Gas-Actuated Fastening System

Fastening into hard concrete or steel can be a challenge. But the newest generation in gas fastening is finally here. The innovative Hilti GX 120 is ruggedly built, perfectly balanced and designed with professionals like you in mind. With its comfortable design, reliability and efficient features, the GX 120 takes drywall track fastening productivity to new heights.

Advantages

- First LED gas gauge helps you avoid running out of gas unexpectedly
- No battery to charge ever
- Reliable electronic gas injection system for consistent fastening
- Versatile, high performance fastening system over a wide range temperatures
- Slim, streamlined design for easy access even in tight corners and narrow tracks
- Drives 750 fasteners with a single gas can, magazine holds 40 fasteners for greater efficiency and higher productivity

It's a gas



LED gauge shows how much gas is left in the can. No more running out of gas in the middle of a job!

Optimum fastenings



Nose piece can easily be adjusted according to base material for proper fastenings

Higher productivity



No battery to charge – ever

Gas-Actuated Fastener Program

Item No.	Description
274638	GX 120 Gas-Actuated Fastening Tool System with 40 fastener magazine Includes tool, detachable support leg, tool support, nail punch set, ear protectors, safety glasses, cleaning cloth and operating instructions in an impact-resistant plastic toolbox

Package content: 750 fasteners and one gas canister

Description	Shank	Length	Items No.	Suitable base material
X-GN 20 MX Combo	0.118	3/4"	226933	Concrete/Block/Masonry
X-GN 27 MX Combo	0.118	1"	226934	Concrete/Block/Masonry
X-GN 32 MX Combo	0.118	1-1/4"	226935	Concrete/Block/Masonry
X-GN 39 MX Combo	0.118	1-5/8"	226936	Concrete/Block/Masonry
X-GHP 18 MX Combo	0.118	11/16"	226931	Hard Concrete/Steel
X-GHP 20 MX Combo	0.118	3/4"	226932	Hard Concrete/Steel
X-EGN 14 MX Combo	0.118	1/2"	226930	Steel

Technical Data

Fastener range	1/2" - 1-5/8"
Power source	GC 22 (gas canister)
Magazine capacity	40 collated fasteners
Dimensions (LxWxH)	17x5.25x15.5 in.
Weight (with fasteners)	7.9 lbs

Application Accessories

Item No.	Description
39540	Holder X-120 PHD (for DELTA®)
39545	Holder X-120 PHP (for Platon)
39619	Holder X-120 WH (magnetic washer holder)



Application overview

	Concrete block/masonry	Standard concrete	Hard concrete	Steel
X-EGN steel nail Lengths: 1/2" (14 mm)				●
Special X-GHP nail Lengths: 11/16", 3/4" (18, 20 mm)		●	●	●
Standard X-GN nail Length: 3/4", 1", 1-1/4", 1-5/8" (20, 27, 32, 39 mm)	●	●		

● Hilti recommended ● May be suitable, depending upon application conditions

Now with 2 Years NO COST

HILTI

LIFETIME SERVICE™

Lifetime

REPAIR COST LIMIT

2 Years

NO COSTS

Lifetime

MANUFACTURERS WARRANTY

*Some limitations apply. Contact Hilti for details.

Let's get things straight.

Hilti PRI 2 Rotating Laser

- Fully automatic horizontal and vertical leveling
- 360° remote control use
- Out of level indicator reduces errors
- 4 handle Hilti design for added tool protection and easy of handling
- Optional rechargeable battery back for hours of continued use



Hilti. Outperform. Outlast.